Released under the Open Data Commons Attribution License (ODC-BY 1.0). You are free to copy, distribute, use, modify, transform, build upon, and produce derived works from our data as long as you attribute any public use of the data, or works produced from the data, in the manner specified in the license. Read the full ODC-BY 1.0 license text for the exact terms that apply. Access to this work was provided by the University of Maryland, Baltimore County (UMBC) ScholarWorks@UMBC digital repository on the Maryland Shared Open Access (MD-SOAR) platform.

# Please provide feedback

Please support the ScholarWorks@UMBC repository by emailing <u>scholarworks-group@umbc.edu</u> and telling us what having access to this work means to you and why it's important to you. Thank you.

## In silico dermoscopy with detailed subsurface scattering

B. Seipp<sup>1,2</sup>, M. Olano<sup>1</sup> & A. Badano<sup>2</sup>

<sup>1</sup>Department of Computer Science, University of Maryland, Baltimore County. Baltimore, MD 1250, USA.
<sup>2</sup>Office of Science and Engineering Laboratories, CDRH/U.S. FDA, Silver Spring, MD 20993, USA.

#### Abstract

We describe an approach to modeling dermoscopy, the imaging modality for the examination of skin lesions, using accurate subsurface scattering in human skin. We make use of an open-source, path-tracing program with advanced physics models as a rendering tool. Rendered scenes are based on biological details from human skin, such as layering, optical properties, and lesion variability, as well as on the properties of the image acquisition device. Preliminary results suggest that this can be an efficient and effective way to generate arbitrarily large datasets of fully featured images with known classification labels.

#### 1. Introduction and Scene Description

Large and well curated image databases are needed for the training, testing, and performance evaluation of digital dermoscopy devices for skin cancer that rely on algorithmic decision making [EKN\*17]. Current databases are relatively small, poorly annotated and the procedures to determine the truth label associated with each image suffer from uncertainty. This project aims at developing an in silico computational tool to generate image databases of annotated photo-realistic images of both normal and cancerous skin conditions. We use an open-source path-based Monte Carlo ray tracer (PBRT [PH10]) to render custom skin and lesion models, defined by the absorption and scattering coefficients for each distinctive skin layer.

Our design allows the user to specify several key parameters to create a scene file compatible with PBRT. Each image is obtained by following the paths of simulated photons through the skin layers in the scene.

We modeled a scene mimicking features similar to the practical use of a dermatoscope during an examination. The dermatoscopic camera is modeled with as an ideal sensor with  $512 \times 512$  pixels, covering an area of 14 mm with a field of view of 90°. LED source lights commonly found in such devices are modeled as point lights in the scene.

Human skin has a complex structure and is challenging to model but can be simplified into several layers consisting of homogeneous materials with shared optical properties [MM02, BGT11a, DWd\*08]. We modeled four layers: muscle, subcutaneous fat, dermis, and epidermis [BGT11b]. The boundaries between layers are modeled as triangle meshes perturbed by Perlin noise [Per02]. For added realism on the epidermis a depth map was used to model surface texture.

We introduced a lesion model to simulate the presence of a can-

cerous growth. The discrete geometry of each skin layer in the model allows for skin lesions to be trivially inserted within the boundaries of any given layer. For demonstration, we have chosen to use lesion optical properties selected to create color contrast between the inserted lesion and the surrounding skin.

### 2. Future Work and Conclusion

Grounding skin boundary parameters to biological attributes would help to more accurately model the subsurface geometry of the scene. Similarly, expanding the computations to include wavelength-dependent optical properties would allow for a more accurate transport albedo. As the model's components become more sophisticated further subdividing layers by more subtle distinctions might be needed. The model already allows for an arbitrarily high number of subdivisions of skin into subsurface layers.

Future work will implement a more realistic lesion model  $[dSBZ^*15]$ . This model will be time-dependent to allow for accurate tags to be applied to images for use in deep learning algorithms.

Testing the fidelity of the model is a challenging problem. A popular method to investigate the realism of synthetic image datasets in radiology is to perform a "fool the human" test [PSZ\*15], which is a modification of Turing's test on machine intelligence [Tur50]. A better approach should look at the effect of training and testing on sets of synthetic and patient images in terms of algorithm efficiency and diagnostic performance similar to the study described by Cha *et al.* [CPP\*19].

By performing photon transport with an accurate subsurface scattering model we can generate a set of images grounded in physical and biological measurements of human skin. This work continues to move towards fully featured datasets of dermatoscopic images rendered in silico.

#### References

- [BGT11a] BASHKATOV A., GENINA E., TUCHIN V.: Optical properties of skin, subcutaneous, and muscle tissues: A review. Journal of Innovative Optical Health Sciences 04 (01 2011). doi:10.1142/ S1793545811001319.1
- [BGT11b] BASHKATOV A. N., GENINA E. A., TUCHIN V. V.: Optical properties of skin, subcutaneous, and muscle tissues: a review. *Journal* of Innovative Optical Health Sciences 4, 01 (2011), 9–38. 1
- [CPP\*19] CHA K. H., PETRICK N., PEZESHK A., GRAFF C. G., SHARMA D., BADAL A., BADANO A., SAHINER B.: Reducing overfitting of a deep learning breast mass detection algorithm in mammography using synthetic images. In *Medical Imaging 2019: Computer-Aided Diagnosis* (2019), vol. 10950, International Society for Optics and Photonics, p. 1095004. 1
- [dSBZ\*15] DE SISTERNES L., BRANKOV J. G., ZYSK A. M., SCHMIDT R. A., NISHIKAWA R. M., WERNICK M. N.: A computational model to generate simulated three-dimensional breast masses. *Medical Physics* 42, 2 (2015), 1098–1118. URL: http://scitation.aip.org/content/aapm/ journal/medphys/42/2/10.1118/1.4905232, doi:http: //dx.doi.org/10.1118/1.4905232.1
- [DWd\*08] DONNER C., WEYRICH T., D'EON E., RAMAMOORTHI R., RUSINKIEWICZ S.: A layered, heterogeneous reflectance model for acquiring and rendering human skin. ACM Trans. Graph. 27, 5 (Dec. 2008), 140:1–140:12. URL: http://doi.acm.org/10.1145/ 1409060.1409093, doi:10.1145/1409060.1409093. 1
- [EKN\*17] ESTEVA A., KUPREL B., NOVOA R. A., KO J., SWETTER S. M., BLAU H. M., THRUN S.: Dermatologist-level classification of skin cancer with deep neural networks. *Nature* 542 (2017), 115–118. 1
- [MM02] MEGLINSKI I. V., MATCHER S. J.: Quantitative assessment of skin layers absorption and skin reflectance spectra simulation in the visible and near-infrared spectral regions. *Physiological measurement* 23, 4 (2002), 741. 1
- [Per02] PERLIN K.: Improving noise. In ACM transactions on graphics (TOG) (2002), vol. 21, ACM, pp. 681–682. 1
- [PH10] PHARR M., HUMPHREYS G.: Physically Based Rendering, Second Edition: From Theory To Implementation, 2nd ed. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 2010. 1
- [PSZ\*15] PEZESHK A., SAHINER B., ZENG R., WUNDERLICH A., CHEN W., PETRICK N.: Seamless insertion of pulmonary nodules in chest ct images. *IEEE Transactions on Biomedical Engineering* 62, 12 (Dec 2015), 2812–2827. doi:10.1109/TEME.2015.2445054.1
- [Tur50] TURING A. M.: Computing machinery and intelligence. Mind 59 (1950), 433–460. 1